

Project:

Vestas V162 A alternative

Licensed user:

SIA Estonian, Latvian & Lithuanian environment

Vilandes 3-6

LV-1010 Riga

0037167242411

Kristiana / kristiana@environment.lv

Calculated:

14/07/2025 5:35 pm/4.0.547

## DECIBEL - Assumptions for noise calculation

Calculation: Vestas V162-6.2 MW STE A alternative

Noise calculation model:

Danish low frequency 2019

Wind speed (at 10 m height):

6.0 m/s - 8.0 m/s, step 2.0 m/s

Terrain reduction:

-1.5 dB(A) Onshore

-3 dB(A) Offshore

Meteorological coefficient, CO:

Selected option: Fixed value: 0.0 dB

Type of demand in calculation:

1: WTG noise is compared to demand (DK, DE, SE, NL etc.)

Noise values in calculation:

All noise values are mean values (Lwa) (Normal)

Pure tones:

Pure tones penalty is added to total noise impact at receptors

Noise sensitive area

Height above ground level, when no value in NSA object:

1.5 m; Don't allow override of model height with height from NSA object

Uncertainty margin:

0.0 dB; Uncertainty margin in NSA has priority

Deviation from "official" noise demands. Negative is more restrictive, positive is less restrictive.:

0.0 dB(A)

Low frequency calculation

All coordinates are in

Geo [deg]-WGS84

WTG: VESTAS V162-6.2 6200 162.0 !O!

Noise: Vestas V162-6.2 STE

Source	Source/Date	Creator	Edited
Tehniska specifikacija	28/05/2024	USER	28/05/2024 11:50 am

Status	Hub height [m]	Wind speed [m/s]	Low frequency data													
			LwA,ref	10.0	12.5	16.0	20.0	25.0	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0	125.0	160.0
			[dB(A)]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
From other hub height	166.0	6.0	95.2	39.8	45.9	51.6	56.9	62.2	67.2	72.2	77.1	81.1	84.3	87.1	89.5	91.6
From other hub height	166.0	8.0	95.3	40.8	46.8	52.3	57.5	62.8	67.7	72.6	77.4	81.4	84.5	87.2	89.6	91.7

Noise sensitive area: 76740010016001 Kalnieš i 2 Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740010018001 Avenaji Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz 12.5 Hz 16.0 Hz 20.0 Hz 25.0 Hz 31.5 Hz 40.0 Hz 50.0 Hz 63.0 Hz 80.0 Hz 100.0 Hz 125.0 Hz 160.0 Hz  
[dB] [dB] [dB] [dB] [dB] [dB] [dB] [dB] [dB] [dB] [dB] [dB] [dB]  
4.9 5.9 4.6 6.6 8.4 10.8 11.4 13.0 16.6 19.7 21.2 20.2 21.2

Project:

Vestas V162 A alternative

Licensed user:

SIA Estonian, Latvian & Lithuanian environment

Vilandes 3-6

LV-1010 Riga

0037167242411

Kristiana / kristiana@environment.lv

Calculated:

14/07/2025 5:35 pm/4.0.547

## DECIBEL - Assumptions for noise calculation

Calculation: Vestas V162-6.2 MW STE A alternative

Pure tone penalty: 0 dB

Noise sensitive area: 76740010032001 Linu Diki Noise sensitive point: Danish 2019 low frequency - Regular dwell

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740010060001 Viktorovka Noise sensitive point: Danish 2019 low frequency - Regular dw

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740010061001 Maksimova Noise sensitive point: Danish 2019 low frequency - Regular dw

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740010074001 Tebeci Noise sensitive point: Danish 2019 low frequency - Regular dwelling

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Project:

Vestas V162 A alternative

Licensed user:

SIA Estonian, Latvian & Lithuanian environment

Vilandes 3-6

LV-1010 Riga

0037167242411

Kristiana / kristiana@environment.lv

Calculated:

14/07/2025 5:35 pm/4.0.547

## DECIBEL - Assumptions for noise calculation

Calculation: Vestas V162-6.2 MW STE A alternative

Noise sensitive area: 76740010076001 Malova Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740010090001 Veveru majas Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740010099001 Cinguli Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020002001 Lielo Oriš u 2 maju zeme Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Project:

Vestas V162 A alternative

Licensed user:

SIA Estonian, Latvian & Lithuanian environment

Vilandes 3-6

LV-1010 Riga

0037167242411

Kristiana / kristiana@environment.lv

Calculated:

14/07/2025 5:35 pm/4.0.547

## DECIBEL - Assumptions for noise calculation

Calculation: Vestas V162-6.2 MW STE A alternative

Noise sensitive area: 76740020004001 Sporanu majas Noise sensitive point: Danish 2019 low frequency - Regular

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020018001 Riteniš i Noise sensitive point: Danish 2019 low frequency - Regular dwell

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020022001 Vetras Noise sensitive point: Danish 2019 low frequency - Regular dwelling

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020035001 Apš upes Noise sensitive point: Danish 2019 low frequency - Regular dwell

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Project:

Vestas V162 A alternative

Licensed user:

SIA Estonian, Latvian & Lithuanian environment

Vilandes 3-6

LV-1010 Riga

0037167242411

Kristiana / kristiana@environment.lv

Calculated:

14/07/2025 5:35 pm/4.0.547

## DECIBEL - Assumptions for noise calculation

Calculation: Vestas V162-6.2 MW STE A alternative

Noise sensitive area: 76740020036001 Mež abele Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020073012 Grovani Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020144001 Dzitari Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020144013 Jaundzitari Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Project:

Vestas V162 A alternative

Licensed user:

SIA Estonian, Latvian & Lithuanian environment

Vilandes 3-6

LV-1010 Riga

0037167242411

Kristiana / kristiana@environment.lv

Calculated:

14/07/2025 5:35 pm/4.0.547

## DECIBEL - Assumptions for noise calculation

Calculation: Vestas V162-6.2 MW STE A alternative

Noise sensitive area: 76740020146001 Brencani Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020154001 Irbeni Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020156001 Maurini Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020165001 Kamenes Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Project:

Vestas V162 A alternative

Licensed user:

SIA Estonian, Latvian & Lithuanian environment

Vilandes 3-6

LV-1010 Riga

0037167242411

Kristiana / kristiana@environment.lv

Calculated:

14/07/2025 5:35 pm/4.0.547

## DECIBEL - Assumptions for noise calculation

Calculation: Vestas V162-6.2 MW STE A alternative

Noise sensitive area: 76740020167001 Zemesbites Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020167007 Vecas Zemesbites Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020168001 Zirnekliš i Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020169001 Purmala Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Project:

Vestas V162 A alternative

Licensed user:

SIA Estonian, Latvian & Lithuanian environment

Vilandes 3-6

LV-1010 Riga

0037167242411

Kristiana / kristiana@environment.lv

Calculated:

14/07/2025 5:35 pm/4.0.547

## DECIBEL - Assumptions for noise calculation

Calculation: Vestas V162-6.2 MW STE A alternative

Noise sensitive area: 76740020172001 Lidumi Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020195001 Rapš i Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020196001 Uzulini Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020199001 Sirmiš i Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB



Project:

Vestas V162 A alternative

Licensed user:

SIA Estonian, Latvian & Lithuanian environment

Vilandes 3-6

LV-1010 Riga

0037167242411

Kristiana / kristiana@environment.lv

Calculated:

14/07/2025 5:35 pm/4.0.547

## DECIBEL - Assumptions for noise calculation

Calculation: Vestas V162-6.2 MW STE A alternative

Noise sensitive area: 76740020200001 Mieziš i Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020200004 Mieziš i Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020245004 Vilniš i Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020245012 Celmalas Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Project:

Vestas V162 A alternative

Licensed user:

SIA Estonian, Latvian & Lithuanian environment

Vilandes 3-6

LV-1010 Riga

0037167242411

Kristiana / kristiana@environment.lv

Calculated:

14/07/2025 5:35 pm/4.0.547

## DECIBEL - Assumptions for noise calculation

Calculation: Vestas V162-6.2 MW STE A alternative

Noise sensitive area: 76740020281001 Ivaiš i Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020285001 Gabri Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740020326001 Smelteru kapseta Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740030004001 Jaundzelzava Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Project:

Vestas V162 A alternative

Licensed user:

SIA Estonian, Latvian & Lithuanian environment

Vilandes 3-6

LV-1010 Riga

0037167242411

Kristiana / kristiana@environment.lv

Calculated:

14/07/2025 5:35 pm/4.0.547

## DECIBEL - Assumptions for noise calculation

Calculation: Vestas V162-6.2 MW STE A alternative

Noise sensitive area: 76740030010001 Virsaiš i Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740030024001 Kalnieš i 2 Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740030039001 Ievaiš i Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740030139001 Zemnieka seta Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Project:

Vestas V162 A alternative

Licensed user:

SIA Estonian, Latvian & Lithuanian environment

Vilandes 3-6

LV-1010 Riga

0037167242411

Kristiana / kristiana@environment.lv

Calculated:

14/07/2025 5:35 pm/4.0.547

## DECIBEL - Assumptions for noise calculation

Calculation: Vestas V162-6.2 MW STE A alternative

Noise sensitive area: 76740040014001 Bucinieki Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740040026001 Zelta Dibens Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740040040001 Viesani Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740040055001 Kalnbirzes Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Project:

Vestas V162 A alternative

Licensed user:

SIA Estonian, Latvian & Lithuanian environment  
Vilandes 3-6  
LV-1010 Riga  
0037167242411  
Kristiana / kristiana@environment.lv  
Calculated:  
14/07/2025 5:35 pm/4.0.547

## DECIBEL - Assumptions for noise calculation

Calculation: Vestas V162-6.2 MW STE A alternative

Noise sensitive area: 76740040169001 Spridiš i 3 Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]  
20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740060002001 Laimnieki Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]  
20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740060014001 Briež udarzs Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]  
20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740060026001 Oš i Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]  
20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Project:

Vestas V162 A alternative

Licensed user:

SIA Estonian, Latvian & Lithuanian environment

Vilandes 3-6

LV-1010 Riga

0037167242411

Kristiana / kristiana@environment.lv

Calculated:

14/07/2025 5:35 pm/4.0.547

## DECIBEL - Assumptions for noise calculation

Calculation: Vestas V162-6.2 MW STE A alternative

Noise sensitive area: 76740060037001 Berzainites Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740060042001 Mež noras Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740060047001 Avotini Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740060111001 Rozes Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Project:

Vestas V162 A alternative

Licensed user:

SIA Estonian, Latvian & Lithuanian environment

Vilandes 3-6

LV-1010 Riga

0037167242411

Kristiana / kristiana@environment.lv

Calculated:

14/07/2025 5:35 pm/4.0.547

## DECIBEL - Assumptions for noise calculation

Calculation: Vestas V162-6.2 MW STE A alternative

Noise sensitive area: 76740060113001 Cielavinas Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740060116001 Rubeniš i Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740060121001 Skalbes Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740060147001 Mozuli Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Project:

Vestas V162 A alternative

Licensed user:

SIA Estonian, Latvian & Lithuanian environment

Vilandes 3-6

LV-1010 Riga

0037167242411

Kristiana / kristiana@environment.lv

Calculated:

14/07/2025 5:35 pm/4.0.547

## DECIBEL - Assumptions for noise calculation

Calculation: Vestas V162-6.2 MW STE A alternative

Noise sensitive area: 76740060161001 Mež otnes Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76740060173001 Dzeniš i Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76820020012001 Rubeni Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76820020107001 Driveniš ki Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB



Project:

Vestas V162 A alternative

Licensed user:

SIA Estonian, Latvian & Lithuanian environment

Vilandes 3-6

LV-1010 Riga

0037167242411

Kristiana / kristiana@environment.lv

Calculated:

14/07/2025 5:35 pm/4.0.547

## DECIBEL - Assumptions for noise calculation

Calculation: Vestas V162-6.2 MW STE A alternative

Noise sensitive area: 76820020123001 Verdini Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76820020210001 Purvietas Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76820020212001 Purvietinas Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB

Noise sensitive area: 76820020454001 Gaitnieki Noise sensitive point: Danish 2019 low frequency - Regular dwellings

Predefined calculation standard: Regular dwellings

Immission height(a.g.l.): Use standard value from calculation model

Uncertainty margin: 0.0 dB

No temporal binning

Noise demand:

6.0 [m/s] 8.0 [m/s]

20.0 dB(A) 20.0 dB(A)

No distance demand

dLsigma

10.0 Hz	12.5 Hz	16.0 Hz	20.0 Hz	25.0 Hz	31.5 Hz	40.0 Hz	50.0 Hz	63.0 Hz	80.0 Hz	100.0 Hz	125.0 Hz	160.0 Hz
[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]	[dB]
4.9	5.9	4.6	6.6	8.4	10.8	11.4	13.0	16.6	19.7	21.2	20.2	21.2

Pure tone penalty: 0 dB